



CONSTRUCTION MATERIALS REGULATION (305/2011/EU) DECLARATION OF CONFORMITY

PRODUCER: NUR KİREÇ SAN. TİC. ve PAZ. LTD. ŞTİ.
ADDRESS: İNCİRLİK CUMHURİYET MAH. ÇİMENTO BULV. NO:13
PK: 01965 YÜREĞİR / ADANA / TURKEY
TELEPHONE: +90 322 332 96 46
WEB: www.nurkirec.com.tr
www.nurkim.com.tr

We declare that our product for name, type and purpose written below, is produced in accordance with the requirements of "305/2011/EU Building Materials Regulation".

TRADE NAME: NUR YAPI KİMYASALLARI
PRODUCT NAME: HYDRO-G10 / SET
PRODUCT DESCRIPTION: NORMAL CEMENT BASED, LIQUID APPLIED
WATERPROOFING MATERIAL WITH CRACKED BRIDGING,
RESISTANCE TO CHLORIDE AND LIME WATER FEATURES
RELATED STANDARD: TS EN 14891 : 04.2017 (TYPE: CM, CLASS: P)
CONFIRMATION SYSTEM: SYSTEM-3
DATE OF ISSUE: 02.01.2018

TECHNICAL PROPERTIES:

INITIAL ADHESION STRENGTH:	$\geq 0,5 \text{ N/mm}^2$
ADHESION STRENGTH AFTER HEAT AGEING:	$\geq 0,5 \text{ N/mm}^2$
ADHESION STRENGTH AFTER FREEZE-THAW CYCLES:	$\geq 0,5 \text{ N/mm}^2$
ADHESION STR. AFTER CONTACT WITH WATER:	$\geq 0,5 \text{ N/mm}^2$
ADHESION STR. AFTER CONTACT WITH LIMEWATER:	$\geq 0,5 \text{ N/mm}^2$
ADHESION STR. AFTER CONTACT WITH CHLORINATED WATER:	$\geq 0,5 \text{ N/mm}^2$
WATER IMPERMEABILITY:	$\leq 20 \text{ g mass gain}$
CRACK BRIDGING ABILITY:	$\geq 0,75 \text{ mm (+ 20°C)}$
TIME REQUIRED FOR UPPER APPLICATION:	3 days

