

**PLASTER MORTARS**

**ADHESIVE MORTARS**

**INSULATION BOARD PRODUCTS**

**REPAIR MORTARS**

**FLOOR SURFACE MORTARS**

**WATER INSULATION PRODUCTS**

**PRIMER PRODUCTS**

**MORTAR - CONCRETE ADDITIVES**

**GROUTING MORTARS**



**NUR**  
**YAPI**  
KİMYASALLARI

[nurkim.com.tr](http://nurkim.com.tr)



<b>4</b>	<b>PLASTER MORTARS</b>
<b>10</b>	<b>ADHESIVE MORTARS</b>
<b>12</b>	<b>INSULATION BOARD PRODUCTS</b>
<b>14</b>	<b>REPAIR MORTARS</b>
<b>16</b>	<b>FLOOR SURFACE MORTARS</b>
<b>18</b>	<b>WATER INSULATION PRODUCTS</b>
<b>22</b>	<b>MORTAR - CONCRETE ADDITIVES</b>
<b>24</b>	<b>PRIMER PRODUCTS</b>
<b>26</b>	<b>GROUTING MORTARS</b>

[nurkim.com.tr](http://nurkim.com.tr)[nurkirec.com.tr](http://nurkirec.com.tr)

In 1984, founded by Arif ZALOĞLU, Nur Kireç San.Tic. ve Paz. Ltd.Şti. has been serving to their customers by the brand names of "NUR KİREÇ" and "NUR AGREGA" for more than 30 years with the facilities of aggregate plant, lime quarries, lime kilns, lime slaking facility in Adana city in TURKEY. Company increased it's daily lime production capacity to 1.250 tons/day through the investments in 2015. Nur Kireç supplies aggregate (CaCO<sub>3</sub>), quicklime (CaO) and hydrated lime (Ca(OH)<sub>2</sub>) products to iron and steel plants, aerated concrete plants, gypsum plants, construction chemicals plants, ready-mix concrete plants, water treatment plants, sugar plants, thermal power plants, etc. and construction sector. Nur Kireç exports its products to different countries all around the world.

At May of 2015, company built a new construction chemicals plant with "NUR YAPI KİMYASALLARI" brand name, which has the one of the highest production capacity in TURKEY as 1.200 tones/day. In this plant, company started to produce cement based plasters for indoors and outdoors, adhesives for ceramic-tile-granite-marble-decorative elements, grouting mortars, floor levelling mortars, repairing mortars, water isolation products, primer products, concrete curing products and mortar additives. As a result of hard work of the experienced technical team at the modern R&D laboratory, Nur Yapı Kimyasalları lives the excitement and pride of serving to its customers with its durable, high quality products that provides innovative solutions in the construction sector in Turkey and in the world.





# PLASTER MORTARS





## G-2000

PROPERTIES

Grey cement-based, reinforced with fiber and chemical additives, 1st layer coarse hand plaster for interiors and exteriors.

## COARSE HAND PLASTER

CONSUMPTION

1,25 m<sup>2</sup> / 35 kg package  
(Thickness: 2 cm)

CERTIFICATES



PACKAGE

35 Kg Kraft Package  
54 Package/Pallet



## G-1200

PROPERTIES

Grey cement-based, reinforced with fiber and chemical additives, resistant to water and moisture, 1st layer hand plaster for interiors and exteriors.

## HAND PLASTER

CONSUMPTION

3 m<sup>2</sup> / 35 kg package  
(Thickness: 1 cm)

CERTIFICATES



PACKAGE

35 Kg Kraft Package  
54 Package/Pallet



## W-1200

PROPERTIES

White cement-based, reinforced with fiber and chemical additives, resistant to water and moisture, 1st layer hand plaster for interiors and exteriors.

## HAND PLASTER

CONSUMPTION

3 m<sup>2</sup> / 35 kg package  
(Thickness: 1 cm)

CERTIFICATES



PACKAGE

35 Kg Kraft Package  
54 Package/Pallet



## G-800

PROPERTIES

Grey cement-based, reinforced with chemical additives, resistant to water and moisture, final layer fine hand plaster for interiors and exteriors.

## FINE HAND PLASTER

CONSUMPTION

10 m<sup>2</sup> / 35 kg package  
(Thickness: 2 mm)

CERTIFICATES



PACKAGE

35 Kg Kraft Package  
54 Package/Pallet



## W-800

PROPERTIES

White cement-based, reinforced chemical additives, resistant to water and moisture, final layer fine hand plaster for interiors and exteriors.

## FINE HAND PLASTER

CONSUMPTION

10 m<sup>2</sup> / 35 kg package  
(Thickness: 2 mm)

CERTIFICATES



PACKAGE

35 Kg Kraft Package  
54 Package/Pallet



## W-100

### PROPERTIES

White cement-based, reinforced with chemical additives, resistant to water and moisture, high covering featured, finishing hand plaster for interiors and exteriors with satiny smooth surface before paint.

### CONSUMPTION

16m<sup>2</sup> / 20 kg package  
(Thickness: 1 mm)

### CERTIFICATES



### PACKAGE

20 Kg Kraft Package  
64 Package/Pallet



## G-MAK

### PROPERTIES

Grey cement-based, reinforced with fiber, perlite and chemical additives, resistant to water and moisture, 1st layer machine plaster for interiors and exteriors which provides smooth surface at one layer application.

### CONSUMPTION

3 m<sup>2</sup> / 35 kg package  
(Thickness: 1 cm)

### CERTIFICATES



### PACKAGE

35 Kg Kraft Package  
54 Package/Pallet



## W-DECO

### PROPERTIES

White cement-based, mineral textured, reinforced with chemical additives, resistant to water and moisture, high covering featured, exterior decorative plaster which is applied by hand to provide a decorative grain textured surface.

### CONSUMPTION

10 m<sup>2</sup> / 25 kg package  
(Thickness: 2 mm)

### CERTIFICATES



### PACKAGE

25 Kg Kraft Package  
64 Package/Pallet



## W-DECO/L

### PROPERTIES

White cement-based, mineral textured, reinforced with chemical additives, resistant to water and moisture, high covering featured, exterior decorative plaster which is applied by hand to provide a decorative line textured surface.

### CONSUMPTION

10 m<sup>2</sup> / 25 kg package  
(Thickness: 2 mm)

### CERTIFICATES



### PACKAGE

25 Kg Kraft Package  
64 Package/Pallet

## SATIN FINISHING PLASTER

## MACHINE PLASTER

## DECORATIVE PLASTER

## DECORATIVE PLASTER



# ADHESIVE MORTARS





## ALFAFIX

PROPERTIES

Normal setting, grey cement based, tile adhesive (C1).

### CLASS C1 TILE ADHESIVE MORTAR

CONSUMPTION


6,5 m<sup>2</sup> / 25 kg package  
(Thickness: 6 mm  
notched trowel)

CERTIFICATES



PACKAGE

25 Kg Kraft Package  
64 Package/Pallet



## ALFAPLUS

PROPERTIES

Normal setting, grey cement based, tile adhesive with reduced slip (C1T)

### C1T CLASS TILE ADHESIVE MORTAR

CONSUMPTION

6,5 m<sup>2</sup> / 25 kg package  
(Thickness: 6 mm  
notched trowel)

CERTIFICATES



PACKAGE

25 Kg Kraft Package  
64 Package/Pallet



## ALFAMAX

PROPERTIES

Normal setting, grey cement based, tile adhesive with reduced slip and extended open time (C1TE).

### C1TE CLASS TILE ADHESIVE MORTAR

CONSUMPTION

5,5 m<sup>2</sup> / 25 kg package  
(Thickness: 8 mm  
notched trowel)

CERTIFICATES



PACKAGE

25 Kg Kraft Package  
64 Package/Pallet



## ALFAMAX/W

PROPERTIES

Normal setting, white cement based, tile adhesive with reduced slip and extended open time (C1TE).

### C1TE CLASS TILE ADHESIVE MORTAR

CONSUMPTION

5,5 m<sup>2</sup> / 25 kg package  
(Thickness: 8 mm  
notched trowel)

CERTIFICATES



PACKAGE

25 Kg Kraft Package  
64 Package/Pallet



## ALFAFLEX

PROPERTIES

Improved grey cement based, tile adhesive with reduced slip and extended open time (C2TE).

### C2TE CLASS TILE ADHESIVE MORTAR

CONSUMPTION

5,5 m<sup>2</sup> / 25 kg package  
(Thickness: 10 mm  
notched trowel)

CERTIFICATES



PACKAGE

25 Kg Kraft Package  
64 Package/Pallet



## ALFAFLEX/W

### PROPERTIES

Improved white cement based, tile adhesive with reduced slip and extended open time (C2TE).

### CONSUMPTION

5,5 m<sup>2</sup> / 25 kg package  
(Thickness: 10 mm  
notched trowel)

### CERTIFICATES



### PACKAGE

25 Kg Kraft Package  
64 Package/Pallet

## C2TE CLASS TILE ADHESIVE MORTAR



## ALFAFLEX/S1

### PROPERTIES

Improved grey cement based, deformable-flex, tile adhesive with reduced slip and extended open time (C2TES1).

### CONSUMPTION

5,5 m<sup>2</sup> / 25 kg package  
(Thickness: 10 mm  
notched trowel)

### CERTIFICATES



### PACKAGE

25 Kg Kraft Package  
64 Package/Pallet

## C2TES1 CLASS TILE ADHESIVE MORTAR



## ALFAFLEX/WS1

### PROPERTIES

Improved white cement based, deformable-flex, tile adhesive with reduced slip and extended open time (C2TES1).

### CONSUMPTION

5,5 m<sup>2</sup> / 25 kg package  
(Thickness: 10 mm  
notched trowel)

### CERTIFICATES



### PACKAGE

25 Kg Kraft Package  
64 Package/Pallet

## C2TES1 CLASS CERAMIC ADHESIVE MORTAR



## ALFAFLEX/S2

### PROPERTIES

Improved grey cement based, highly deformable-super flex, tile adhesive with reduced slip and extended open time (C2TES2).

### CONSUMPTION

5,5 m<sup>2</sup> / 25 kg package  
(Thickness: 10 mm  
notched trowel)

### CERTIFICATES



### PACKAGE

25 Kg Kraft Package  
64 Package/Pallet

## C2TES2 CLASS TILE ADHESIVE MORTAR



## ALFAFLEX/WS2

### PROPERTIES

Improved white cement based, highly deformable-super flex, tile adhesive with reduced slip and extended open time (C2TES2).

### CONSUMPTION

5,5 m<sup>2</sup> / 25 kg package  
(Thickness: 10 mm  
notched trowel)

### CERTIFICATES



### PACKAGE

25 Kg Kraft Package  
64 Package/Pallet

## C2TES2 CLASS TILE ADHESIVE MORTAR



## ALFABLOCK

GAS CONCRETE - PUMICE - BRICK MASONRY MORTAR

### PROPERTIES

High performance, reinforced with chemical additives, grey cement based gas concrete-pumice-brick masonry mortar for general purpose.

### CONSUMPTION

9 m<sup>2</sup> / 25 kg package  
(Thickness: 8 mm  
notched trowel)

### CERTIFICATES

TSE  
TS EN 998-2 / 09.01.2017  
CE<sub>17</sub>  
ISO  
9001:2015

### PACKAGE

25 Kg Kraft Package  
64 Package/Pallet



ADHESIVE MORTARS

NUR YAPI KIMYASALLARI

# INSULATION BOARD PRODUCTS





## MANTO-FIX

PROPERTIES

Grey cement based, adhesive for thermal insulation boards with reduced slip and improved adhesion strength.

### ADHESIVE FOR THERMAL INSULATION BOARD

CONSUMPTION

5 m<sup>2</sup> / 25 kg package  
(Thickness: 10 mm  
notched trowel)

CERTIFICATES



PACKAGE

25 Kg Kraft Package  
64 Package/Pallet



## MANTO-PLAST

PROPERTIES

Grey cement-based, reinforced with fiber and chemical additives, resistant to water and moisture, hand plaster for thermal insulation boards.

### PLASTER FOR THERMAL INSULATION BOARD

CONSUMPTION

5 m<sup>2</sup> / 25 kg package  
(Thickness: 4 mm)

CERTIFICATES



PACKAGE

25 Kg Kraft Package  
64 Package/Pallet



# REPAIR MORTARS





## RP-1200

PROPERTIES

Grey cement-based, reinforced with fiber and chemical additives, resistant to water and moisture, non-structural (R2 class), coarse repair mortar for indoors and outdoors with improved adhesion and compressive strength.

### COARSE REPAIR MORTAR

CONSUMPTION

0,4 m<sup>2</sup> / 25 kg package  
(Thickness: 40 mm)

CERTIFICATES



PACKAGE

25 Kg Kraft Package  
64 Package/Pallet



## RP-800

PROPERTIES

Grey cement-based, reinforced with fiber and chemical additives, resistant to water and moisture, non-structural (R2 class), fine repair mortar for indoors and outdoors with improved adhesion and compressive strength.

### FINE REPAIR MORTAR

CONSUMPTION

0,8 m<sup>2</sup> / 25 kg package  
(Thickness: 20 mm)

CERTIFICATES



PACKAGE

25 Kg Kraft Package  
64 Package/Pallet



## RP-GROUT

PROPERTIES

Grey cement-based, reinforced with chemical additives, resistant to water and moisture, resistant to freeze and thaw, non-shrinking, non-expanding self levelling, structural (R4 class) grout-casting-repair mortar with high compressive strength.

### GROUT-CASTING-REPAIR MORTAR

CONSUMPTION

1,2 m<sup>2</sup> / 25 kg package  
(Thickness: 10 mm)

CERTIFICATES



PACKAGE

25 Kg Kraft Package  
64 Package/Pallet



## RP-MAX4

PROPERTIES

Grey cement based, reinforced with fiber and chemical additives, resistant to moisture and water, low chloride permeability, improved high strength, structural (R4 class) repair mortar for indoors and outdoors.

### STRUCTURAL REPAIR MORTAR

CONSUMPTION

0,35 m<sup>2</sup> / 25 kg package  
(Thickness: 40 mm)

CERTIFICATES



PACKAGE

25 Kg Kraft Package  
64 Package/Pallet



## RP-AC

PROPERTIES

Single component coating material containing high quality cements, silica fillers and performance enhancing chemicals used to protect steel reinforcement from corrosion.

### ANTI-CORROSION MORTAR

CONSUMPTION

12-15 m<sup>2</sup> / 25 kg package  
(Thickness: 1 mm)

CERTIFICATES



PACKAGE

25 Kg Kraft Package  
64 Package/Pallet

# FLOOR SURFACE MORTARS





## FL-HARDENER SURFACE HARDENER FOR FRESH CONCRETE MORTAR

<b>PROPERTIES</b>	Cement based, reinforced with mineral fillers and chemical additives, surface hardener for fresh concrete mortar with natural, red and green color options.	<b>CONSUMPTION</b>	5 m <sup>2</sup> / 25 kg package (Natural gray)	<b>CERTIFICATES</b>	TSE TS EN 1504-2 / 10.04.2008	<b>PACKAGE</b>	25 Kg Kraft Package
	3 m <sup>2</sup> / 25 kg package (Other colors)		CE <sub>17</sub> ISO 9001:2015		64 Package/Pallet		



## FL-SELF SELF-LEVELLING FLOOR SCREED MORTAR

<b>PROPERTIES</b>	Grey cement-based, reinforced with chemical additives, non-shrinking and non-expanding self levelling floor screed mortar with high adhesion strength.	<b>CONSUMPTION</b>	4 m <sup>2</sup> / 25 kg package (Thickness: 5 mm)	<b>CERTIFICATES</b>	TSE TS EN 13813 / 02.12.2004	<b>PACKAGE</b>	25 Kg Kraft Package
			CE <sub>17</sub> ISO 9001:2015		64 Package/Pallet		



## FL-MOLD MOULD RELEASE POWDER FOR STAMPED CONCRETE SYSTEMS

<b>PROPERTIES</b>	Cement based powder mold release agent with an aged effect to easily separate mold of stamped concrete surface hardener.	<b>CONSUMPTION</b>	25-50 m <sup>2</sup> / 10 kg package	<b>CERTIFICATES</b>	ISO 9001:2015	<b>PACKAGE</b>	10 Kg Kraft Package
			64 Package/Pallet				



## FL-STAMP SURFACE HARDENER FOR STAMPED CONCRETE SYSTEMS

<b>PROPERTIES</b>	Cement based, quartz filled, reinforced with chemical additives, applied monolithically to the concrete surface, colored, surface hardener for stamped concrete systems.	<b>CONSUMPTION</b>	5-8 m <sup>2</sup> / 25 kg package	<b>CERTIFICATES</b>	TSE TS EN 1504-2 / 10.04.2008	<b>PACKAGE</b>	25 Kg Kraft Package
			CE <sub>17</sub> ISO 9001:2015		64 Package/Pallet		



## CURE-AR WATER BASED CONCRETE CURING MATERIAL

<b>PROPERTIES</b>	Acrylic resin & water based liquid curing material to prevent water loss of surface by creating a film layer, after concrete, screed or surface hardener application.	<b>CONSUMPTION</b>	0,25 kg/m <sup>2</sup> (120 m <sup>2</sup> / 30 kg can)	<b>CERTIFICATES</b>	TSE TS EN 1504-2 / 10.04.2008	<b>PACKAGE</b>	30 Kg Plastic Can
			CE <sub>17</sub> ISO 9001:2015		24 Cans/Pallet		



## CURE-SR SOLVENT BASED CONCRETE CURING MATERIAL

<b>PROPERTIES</b>	Acrylic resin & solvent based liquid curing material to prevent water loss of the concrete surface by creating a film layer after concrete, screed or surface hardener applications.	<b>CONSUMPTION</b>	0,20 kg/m <sup>2</sup> (125 m <sup>2</sup> / 25 kg can)	<b>CERTIFICATES</b>	TSE TS EN 1504-2 / 10.04.2008	<b>PACKAGE</b>	25 Kg Plastic Can
			CE <sub>17</sub> ISO 9001:2015		24 Cans/Pallet		

# WATER INSULATION PRODUCTS





## HYDRO-CRY

### ONE COMPONENT CRYSTALLIZED WATER INSULATION PRODUCT

**PROPERTIES**

Single component, cement based, crystalline waterproofing material that provides permanent water impermeability by penetrating into cement based surfaces and forming insoluble crystals in capillary spaces.

**CONSUMPTION**

16 m<sup>2</sup> / 25 kg package  
(Thickness:  
1 mm x 1 layer)

**CERTIFICATES**



**PACKAGE**

25 Kg Kraft Package  
54 Package/Pallet



## HYDRO-G5/SET

### DOUBLE COMPONENT SEMI-FLEXIBLE WATERPROOFING MORTAR

**PROPERTIES**

Grey cement and polymer emulsion based, antibacterial, highly water repellent, modified with special additives, two-component, semiflexible, water-proofing material.

**CONSUMPTION**

14 m<sup>2</sup> / (20 kg + 5 kg) set  
(Thickness:  
1 mm x 1 layers)

**CERTIFICATES**



**PACKAGE**

Comp.A:  
20 Kg Kraft Package  
Comp.B:  
5 Kg Plastic Can  
72 Set / 2 Pallets



## HYDRO-G10/SET

### DOUBLE COMPONENT FLEXIBLE WATERPROOFING MORTAR

**PROPERTIES**

Grey cement and polymer emulsion based, antibacterial, highly water repellent, modified with special additives, two-component, flexible, water-proofing material.

**CONSUMPTION**

18 m<sup>2</sup> / (20 kg + 10 kg) set  
(Thickness:  
1 mm x 1 layers)

**CERTIFICATES**



**PACKAGE**

Comp.A:  
20 Kg Kraft Package  
Comp.B:  
10 Kg Plastic Can  
60 Set / 2 Pallets



## HYDRO-W10/SET

### DOUBLE COMPONENT FLEXIBLE UV RESISTANT WATERPROOFING MORTAR

**PROPERTIES**

White cement and polymer emulsion based, antibacterial, UV resistant, highly water repellent, modified with special additives, two-component, flexible, water-proofing material.

**CONSUMPTION**

18 m<sup>2</sup> / (20 kg + 10 kg) set  
(Thickness:  
1 mm x 1 layers)

**CERTIFICATES**



**PACKAGE**

Comp.A:  
20 Kg Kraft Package  
Comp.B:  
10 Kg Plastic Can  
60 Set / 2 Pallets



## HYDRO-STOP

### CEMENT BASED WATER PLUG MORTAR

**PROPERTIES**

Cement-based, instant setting water plug mortar with mineral filler and special chemicals that providing a suitable sublayer before waterproofing against water leaks.

**CONSUMPTION**

1,8 kg for 1 liter of gap

**CERTIFICATES**



**PACKAGE**

3 Kg Plastic Bucket  
100 Buckets/Pallet



## HYDRO-LP

### PROPERTIES

Elastomeric resin based, flexible, solvent-free, one component-liquid waterproofing material providing high water impermeability on cementitious surfaces.

## ACRYLIC BASED LIQUID MEMBRANE

### CONSUMPTION

13,3 m<sup>2</sup> / 20 kg Bucket  
(Thickness:  
1 mm x 1 layer)

### CERTIFICATES



### PACKAGE

20 Kg Plastic Bucket  
36 Buckets/Pallet  
3 Kg Plastic Bucket  
100 Buckets/Pallet



## HYDRO-FLEX

### PROPERTIES

Elastomeric resin based, flexible, solvent-free, reinforced with fiber, one component-liquid waterproofing material providing high water impermeability on cementitious surfaces.

### CONSUMPTION

13,3 m<sup>2</sup> / 20 kg Bucket  
(Thickness:  
1 mm x 1 layer)

### CERTIFICATES



### PACKAGE

20 Kg Plastic Bucket  
36 Buckets/Pallet  
3 Kg Plastic Bucket  
100 Buckets/Pallet



## HYDRO-EMP

### PROPERTIES

Water-based, transparent, surface protective emulsion waterproofing material that impregnates to the absorbent surface to provide water-repellent property.

### CONSUMPTION

100-300 m<sup>2</sup> / 30 kg can  
(Thickness:  
1 mm x 1 layer)

### CERTIFICATES



### PACKAGE

30 Kg Plastic Can  
24 Cans/Pallet  
10 Kg Plastic Can  
60 Cans/Pallet  
5 Kg Plastic Can  
72 Cans/Pallet



## BİTÜM-PR

### PROPERTIES

Polymer modified bitumen rubber and water based, single component coating material which is applied to foundations, curtain walls, wet areas, retaining walls, structural elements exposed to seepage water or temporary/continuous water pressure before bitumen based membrane application.

### CONSUMPTION

57-85 m<sup>2</sup> / 17 kg Bucket  
(Thickness:  
1 mm x 1 layer)

### CERTIFICATES



### PACKAGE

17 kg Plastic Bucket  
27 Buckets/Pallet



## BİTÜM-1K

### PROPERTIES

Polymer modified bitumen rubber and water-based, two-component waterproofing material used for the insulation of foundations, curtain walls, wet areas, retaining walls and structural elements which are exposed to seepage water or temporary/continuous water pressure.

### CONSUMPTION

6-15 m<sup>2</sup> / 30 kg Bucket

### CERTIFICATES



### PACKAGE

30 Kg Plastic Bucket  
18 Buckets/Pallet

## SINGLE-COMPONENT BITUMEN-BASED WATERPROOFING MATERIAL



## BITÜM-2K

### PROPERTIES

Polymer modified bitumen rubber and water-based, two-component waterproofing material used for the insulation of foundations, curtain walls, wet areas, retaining walls, external surfaces of wastewater channels and structural elements which are exposed to seepage water or temporary/continuous water pressure.

### DOUBLE-COMPONENT BITUMEN BASED WATERPROOFING MATERIAL

### CONSUMPTION

6-15 m<sup>2</sup> / 8+22 kg  
Bucket

### CERTIFICATES

ISO  
9001:2015

### PACKAGE

8+22 kg  
Plastic Bucket  
18 Buckets/Pallet



# MORTAR CONCRETE ADDITIVES





## ADD-LATEX

### PROPERTIES

Liquid concrete and mortar additive to improve adherence, flexibility, impermeability, workability, chemical resistance features.

## SBR BASED LATEX MORTAR ADDITIVE

### CONSUMPTION

\*Please refer to the Technical Data Sheet.

### CERTIFICATES



### PACKAGE

30 Kg Plastic Can  
24 Cans/Pallet

10 Kg Plastic Can  
60 Cans/Pallet

5 Kg Plastic Can  
72 Cans/Pallet



## ADD-M1

### PROPERTIES

Chlorine-free, liquid, water impermeability additive which reacts with cement and aggregate in concrete and cementious mortars to fill capillary gaps.

## WATER IMPERMEABILITY MORTAR ADDITIVE

### CONSUMPTION

\*Please refer to the Technical Data Sheet.

### CERTIFICATES



### AMBALAJ

30 Kg Plastic Can  
24 Cans/Pallet

10 Kg Plastic Can  
60 Cans/Pallet

5 Kg Plastic Can  
72 Cans/Pallet



## ADD-ANTIFREEZE

### PROPERTIES

Chloride-free, liquid additive that accelerates the setting of cement-based concrete and mortars by increasing the hydration heat of cement and decreasing the freezing point of water, thus ensuring applicability in weather conditions with cold/freezing risk.

## FROST-RESISTANT MORTAR ADDITIVE

### CONSUMPTION

\*Please refer to the Technical Data Sheet.

### CERTIFICATES



### PACKAGE

30 Kg Plastic Can  
24 Cans/Pallet

10 Kg Plastic Can  
60 Cans/Pallet

5 Kg Plastic Can  
72 Cans/Pallet



# PRIMER PRODUCTS





## PRIMER-PL

### PROPERTIES

Acrylic emulsion based, solvent free, plaster primer with mineral fillers, that reduces water absorption of the cementitious surfaces and increases adhesion strength of the smooth cementitious surfaces at indoors and outdoors.

## PRIMER FOR PLASTERS

### CONSUMPTION

85 m<sup>2</sup> / 25 kg bucket  
(Thickness:  
1 mm x 1 layer)

### CERTIFICATES



### PACKAGE

25 Kg Plastic Bucket  
36 Buckets/Pallet  
12 Kg Plastic Bucket  
48 Buckets/Pallet  
3 Kg Plastic Bucket  
100 Buckets/Pallet



## PRIMER-ST

### PROPERTIES

Acrylic emulsion based, solvent-free, general purpose primer to reduce water absorption and to increase adhesion of the application surfaces.

## PRIMER FOR GENERAL PURPOSE

### CONSUMPTION

120 m<sup>2</sup> / 30 kg can  
(Thickness:  
1 mm x 1 layer)

### CERTIFICATES



### PACKAGE

30 Kg Plastic Can  
24 Cans/Pallet  
10 Kg Plastic Can  
60 Cans/Pallet  
5 Kg Plastic Can  
72 Cans/Pallet



## PRIMER-TL

### PROPERTIES

Acrylic emulsion based, solvent-free, surface primer with mineral fillers, to prepare glassy surfaces (ceramic, mosaic, wood, etc.) for coating material fixing applications.

## PRIMER FOR GLASSY SURFACE

### CONSUMPTION

20 m<sup>2</sup> / 3 kg bucket  
(Thickness:  
1 mm x 1 layer)

### CERTIFICATES



### PACKAGE

3 Kg Plastic Bucket  
100 Buckets/Pallet  
1 Kg Plastic Bucket  
256 Buckets/Pallet



# GROUTING MORTARS





## FUGA-SIL

### CG1 CLASS GROUTING MORTAR


#### PROPERTIES

Normal cement based, grouting / joint filler mortar with 21 color options (CG1)

#### CONSUMPTION

Please check the consumption table below.

#### CERTIFICATES



#### PACKAGE

20 Kg Kraft Package  
64 Package/Pallet



## FUGA-SILFLEX

### CG2WA CLASS GROUTING MORTAR


#### PROPERTIES

Improved with additional properties, cement based grouting / joint filler mortar with high abrasion strength and reduced water absorption by it's silicon additive, with 21 color options (CG2WA)

#### CONSUMPTION

Please check the consumption table below.

#### CERTIFICATES



#### PACKAGE

20 Kg Kraft Package  
64 Package/Pallet

## GROUTING COLOR CHART

1ST GRADE COLORS	2ST GRADE COLORS	3ST GRADE COLORS
WHITE	BROWN	BLACK
IVORY	FAWN	ANTHRACITE
CREAM	YELLOW	BLUE
BEIGE	CARAMEL	RED
ANATOLIAN BEIGE	SOMON	ORANGE
CAPPADOCIA BEIGE	ROSE	CACAO
LIGHT GRAY	GRAY	GREEN

LIME  
PRODUCTS

## CL 90 - S

Highly pure - %Ca  $\geq$  90,  
micronised - under 90  $\mu$ m,  
calcium hydrated lime  
(CL 90-S)

PROPERTIES

## CL 90-S HYDRATED LIME

CERTIFICATES



PACKAGE

25 Kg Kraft Package  
50 Package/Palette



## CL 80-S

Pure - %Ca  $\geq$  80,  
micronised - under 200  $\mu$ m,  
calcium hydrated lime  
(CL 80-S)

PROPERTIES

## CL 80-S HYDRATED LIME

CERTIFICATES



PACKAGE

25 Kg Kraft Package  
50 Package/Palette



## CL 80-S

Pure micronised,  
calcium hydrated lime  
for agriculture  
(CL 80-S)

PROPERTIES

## AGRICULTURE LIME

CERTIFICATES



PACKAGE

25 Kg Kraft Package  
50 Package/Palette



## CL 90-Q

Highly pure - %Ca  $\geq$  90,  
granuled, calcium  
quicklime  
(CL 90-S)

PROPERTIES

## CL 90-Q QUICK LIME

CERTIFICATES



PACKAGE

25 Kg PP Package  
50 Package/Palette





[nurkim.com.tr](http://nurkim.com.tr)

 Güzel Cumhuriyet Mah. Çimento Blv. No:23 Yüreğir / Adana / TÜRKİYE

 +90 322 332 96 46  [nurkirec@nurkirec.com.tr](mailto:nurkirec@nurkirec.com.tr)

[www.nurkirec.com.tr](http://www.nurkirec.com.tr)

A  Company  
NUR  
GRUP